

DS-KD8003-IME2 Door Station



Key Feature

- Two-pin wire for power supply and network access
- Access control function
- Noise suppression and echo cancellation
- H.264 video compression
- Low illumination
- Tampering alarm
- Fisheye camera with IR supplement light
- Supports sub-modules' access (max. 8)
- Nametag customization
- Easy to and extend


Specification

Model		DS-KD8003-IME2
System	Processor	Embedded microcontroller
	Operation mode	One touch key



Model		DS-KD8003-IME2
	Operation system	Embedded Linux operation system
Video	Input	200 W super definition camera
	Night shot	Support low light and IR light-supplement mode
	Backlight compensation	Support
	Digital noise reduction	Support
	Wide dynamic	Real wide dynamic
	Field angle	Horizontal 180°, vertical 96°
	Video compression standard	H.264
	Video code stream	Main stream: 1080p@30fps, 720p@30fps (configurable); sub stream: D1
	Video resolution	Main stream: 1920 × 1080, (720p configurable); sub stream: 720 × 480
	Motion detection	Support
	Flash-avoid frequency	50 Hz, 60 Hz
	Audio	Audio intercom
Audio input		Omnidirectional microphone
Audio output		Loudspeaker, 20 cm sound effect > 80db
Audio compression standard		G.711 U
Audio compression rate		64 Kbps
Audio quality		Noise suppression and echo cancellation
Network	Wired network interface	Two-wire transmission
	Protocol	TCP/IP, RTSP
Access control	Relay interface (main module)	2, NC + NO separately draw forth
Interface	RS-485	1 (inter-module connection)
	Alarm input	4
Tamper	Tamper	1
General	Protective level	IP 65
	Button	1
	Power input	24 VDC two-wire power supply (< 16 W) or 12 VDC independent power supply (< 20 W)
	Power output	12 VDC (only for power supply of submodule)
	Working temperature	-40 °C to 60 °C (-40 °F to 140 °F)
	Working humidity	10% to 95%
	Installation	Wall mounting


Typical Application



Available Model

DS-KD8003-IME2

Physical Interface



No.	Description	No.	Description
1	Microphone	6	Nametage
2	Low Illumination IR Supplement Light	7	TAMPER
3	Bult-in Camera	8	Network Interface and Power Supply
4	Loudspeaker	9	Module-connecting Interface (output)
5	Call Button	10	Terminals

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com