

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2013 with regard to energy labelling of electronic displays

| Parameter |  | Parameter or value and precision                                    |   |      | Unit            |
|-----------|--|---|---|------|-----------------|
| 1.        | Supplier's name or trade mark:   | Hisense   |   |      |                 |
|           | Supplier's address:  | HISENSE-PUBLIC<br>CONTACT,PARTIZACESTA 12,3320<br>VELENJE,SLOVENIJA |   |      |                 |
| 2.        | Model identifier:  | 50E7Q   |   |      |                 |
| 3.        | Energy Efficiency Class for Standard Dynamic Range (SDR)   | E   |   |      |                 |
| 4.        | On mode power demand for Standard Dynamic Range (SDR)  | 54  |   |      | W               |
| 5.        | Energy Efficiency Class for High Dynamic Range (HDR)   | G   |   |      |                 |
| 6.        | On mode power demand in High Dynamic Range (HDR), if implemented   | 95  |   |      | W               |
| 7.        | Off mode, power demand, if applicable  | 0,00  |   |      | W               |
| 8.        | Standby mode power demand, if applicable   | 0,50  |   |      | W               |
| 9.        | Networked standby mode power demand, if applicable   | 2,00  |   |      | W               |
| 10.       | Electronic display category  | Television  |   |      |                 |
| 11.       | Size ratio   | 16  | : | 9    |                 |
| 12.       | Screen resolution  | 3840  | x | 2160 | Pixels          |
| 13.       | Screen diagonal  | 126   |   |      | cm              |
| 14.       | Screen diagonal  | 50  |   |      | Inches          |
| 15.       | Visible screen area  | 67,5  |   |      | dm <sup>2</sup> |
| 16.       | Panel technology used  |   |   |      |                 |
| 17.       | Automatic Brightness Control (ABC) available   | No  |   |      |                 |
| 18.       | Voice recognition sensor available   | No  |   |      |                 |
| 19.       | Room presence sensor available   | No  |   |      |                 |
| 20.       | Image refresh frequency rate (default)   | 60  |   |      | Hz              |
| 21.       | Minimum guaranteed availability of software and firmware updates (from the date of end of the placement on the market) | 8   |   |      | Years           |
| 22.       | Minimum guaranteed availability of spare parts (from the date of end of the placement on the market)                   | 7   |   |      | Years           |
| 23.       | Minimum guaranteed product support   | 10  |   |      | Years           |
|           | Minimum duration of the general guarantee offered by the supplier  | 2   |   |      | Years           |
| 24.       | Power supply type:   | Internal  |   |      |                 |
| 25.       | External power supply (non standardized and included in the product box)   |   |   |      |                 |
|           | i.   | -   |   |      |                 |
|           | ii.  | Input voltage   |   |      | - V             |
|           | iii.   | Output voltage  |   |      | - V             |
| 26.       | External standardised power supply (or suitable one if not included in the product box)                                |   |   |      |                 |
|           | i.   | -   |   |      |                 |
|           | ii.  | Required output voltage   |   |      | - V             |
|           | iii.   | Required delivered current (minimum)                                |   |      | - A             |
|           | iv.  | Required current frequency  |   |      | - Hz            |